



PRODUCT DATA SHEET

WALL PANEL BARRANCA



FEATURES

- Available in standard 2”, 4”, 6” and 8” plank widths
- Can be installed on any substrate material
- Strength and durability of extruded aluminum
- Different finishes and colors available


BENEFITS

- Progressive installation
- Access doors available
- Cost-saving labor
- Uniform look over long spans

FIRE RATING

All metal wall panels and associated suspension systems are made entirely of noncombustible materials and meet all known code requirements.

TYPICAL ISOMETRICS & SECTIONS



ALUMINUM

Material to comply with ASTM B 209, alloy and temper recommended by aluminum producer and finish requested, with strength and durability equal to or greater than the properties of the 6063-T6 for painted finishes.


Thickness: 0.047”

WALL PANEL BARRANCA


COLORS & FINISHES

A wide variety of colors and finishes are available. Options shown below are for illustration purposes only. Custom finishes are available on request. Minimum orders and associated lead times may apply to custom options.

ALUMINUM



Polyester
powder coat



Pre-painted or
post-painted




Duranar or Kynar



Enamel paint


WOOD FINISHES



Cherry




Maple



Chestnut



White Birch



Walnut

www.carritec.com

info@carritec.com

575 Boul Morgan, Baie-d'Urfé, QC H9X 3T6

514 457 7779 | 800 610 0179 | 514 457 5559